

AN 1900

Far Field Reference Design for G2iL / G2iL+ (FarField9510-iL)

Rev. 1.0 — 2 April 2010

Application note

Document information

Info	Content
Keywords	UCODE EPC G2, G2iL, G2iL+, Reference Design, Antenna Design, Far Field, Broadband, Aluminum, FarField9510-iL
Abstract	This application note is a reference antenna design description for the UCODE G2iL / G2iL+ IC.



Revision history

Rev	Date	Description
1.0	02.04.2010	First initial release; Author: BFI

Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

1. Far Field Reference Antenna Design

1.1 Geometry

- Dimensions of the design: 95 mm x 10 mm;
- Antenna material: aluminium; thickness 10um;
- Substrate material: PET; thickness 50um;
- Antenna should be matched to following assembled IC impedance:
($Z_{\text{ass. IC}} = 17.3 - j 171.4 \text{ Ohm @ } 915 \text{ MHz @ } P_{\text{IC}} = P_{\text{IC min}} + 0.5\text{dB}$);
 $C_{\text{serial}} = 1.02 \text{ pF}$;





Fig 1. Far Field Reference Design


2. CST Simulation Results

The following simulations are solved using CST with Transient Solver, a commercial 3-D solver for electromagnetic structures used for antenna design and the design of complex RF electronic circuit elements.

2.1 Antenna Impedance

One of the key characteristics of the label antenna is its complex input impedance as a function of frequency. The curves of Antenna_Real Part and Antenna_Imaginary Part of the optimized design are shown in **Fig.2**. The marker is on the position of the resonance frequency from the S11 curve. This shows the matching between the antenna and the assembled IC impedance.





2.2 Return Loss

The antenna impedance on one side and the assembled IC impedance on the other let calculate the return loss, Γ , which show a degree of matching between them (**Equation 1**).

$$\Gamma = \frac{Z_A - Z_{IC}^*}{Z_A + Z_{IC}} \quad (1)$$

The corresponded curve is shown in **Fig 4**. The curve is based on the assumption that the IC impedance remains constant for all frequencies and corresponds to those, measured at 915MHz by $P_{IC} = P_{min\ IC} + 0.5\ dB$.





Fig 4. Far Field design: Return Loss (Marker position 1)



The matched frequency area covers the whole UHF RFID frequency band (860-960 MHz) if the label is placed on a material with an epsilon R value around 2 (e.g. Teflon).

2.3 Antenna Gain

The label radiation properties are shown in Fig 6 - Fig 9. The maximal Gain is 2.1 dBi.







Fig 6. Far Field design: 3D Antenna Gain @ 915MHz







3. Assembly process

3.1 Equipment

- Thermode Test Station TTS 300 from Mühlbauer
- Low force thermode

3.2 Recommended assembly parameters

- Antenna: Alu 10um
- Substrate: PET 50um
- Glue: E&C 13975-11A
- Temperature
 - Upper thermode: 190 °C
 - Lower thermode: 160 °C
- Bonding time: 10 sec.
- Bonding pressure: 1,9 N

4. Legal information

4.1 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

4.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on a weakness or default in the customer application/use or the application/use of customer's third party customer(s) (hereinafter both referred to as "Application"). It is customer's sole responsibility to check whether the NXP Semiconductors product is suitable and fit for the Application planned. Customer has to do all necessary testing for the Application in order to avoid a default of the Application and the product. NXP Semiconductors does not accept any liability in this respect.

- The UHF reference antennas designed by NXP shall only be assembled with NXP UCODE devices.

- No licensing charge applies when using NXP UHF reference antennas with NXP UCODE devices.

- NXP Semiconductors does not indemnify on antenna IP.

- General terms and conditions apply, see <http://www.nxp.com/profile/terms/austria/>

- The design(s), specifications, documentation and other data provided herewith (collectively the "Reference Design") are provided by NXP for use with NXP products. This Reference Design is provided by NXP as an accommodation to user, and on an "as-is" basis. All warranties, representations, or guarantees of any kind with respect to the Reference Design (whether express, implied or statutory) including, without limitation, warranties of merchantability, fitness for a particular purpose, title, or non-infringement, are specifically disclaimed. Without limiting the generality of the foregoing, NXP does not warrant the functionality of the Reference Design for any particular use. Nor does NXP warrant that the Reference Design is error-free, tested, or will function in the manner represented. It is the user's sole responsibility to determine whether the Reference Design is suitable for the user's intended use. It is also user's sole responsibility to determine whether the Reference Design, or any portion thereof, infringes patents, copyrights or other intellectual property rights. No contractual obligations whatsoever are formed, either directly or indirectly, by NXP making this Reference Design available for user's consideration, or by user's ultimate use of the Reference Design. By providing this Reference Design, NXP does not grant a license, express, implied, by estoppel or otherwise, to NXP's or any third party's intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

4.3 Licenses

Purchase of NXP <xxx> components

<License statement text>

4.4 Patents

Notice is herewith given that the subject device uses one or more of the following patents and that each of these patents may have corresponding patents in other jurisdictions.

<Patent ID> — owned by <Company name>

4.5 Trademarks

Notice: All referenced brands, product names, service names and trademarks are property of their respective owners.

UCODE — is a trademark of NXP B.V.

5. List of figures

Fig 1.	Far Field Reference Design	3
Fig 2.	Far Field design: Impedance (Marker position 1)	4
Fig 3.	Far Field design: Impedance (Marker position 2)	5
Fig 4.	Far Field design: Return Loss (Marker position 1).....	6
Fig 5.	Far Field design: Return Loss (Marker position 2).....	7
Fig 6.	Far Field design: 3D Antenna Gain @ 915MHz	8
Fig 7.	Far Field design: 3D Antenna Gain @ 915MHz – label position	9
Fig 8.	Far Field design: 2D Antenna Radiation Pattern @ 915MHz. E-Plane	10
Fig 9.	Far Field design: 2D Antenna Radiation Pattern @ 915MHz. H-Plane	11

6. Contents

1. Far Field Reference Antenna Design.....3

1.1 Geometry3

2. CST Simulation Results4

2.1 Antenna Impedance4

2.2 Return Loss.....6

2.3 Antenna Gain8

3. Assembly process.....12

3.1 Equipment12

3.2 Recommended assembly parameters.....12

4. Legal information13

4.1 Definitions13

4.2 Disclaimers.....13

4.3 Licenses.....13

4.4 Patents.....13

4.5 Trademarks.....13

5. List of figures.....14

6. Contents.....15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.

© NXP B.V. 2010. All rights reserved.

For more information, please visit: <http://www.nxp.com>
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 2 April 2010
Document identifier: 190010