

Table of Contents

1	Title
2	Notes
3	Sensors

Revisions

Rev	Description	Date
X1	Original Release	07-15-15
A	Release	11-3-15

BRKTSTBC-P3115

		RF, Analog & Sensor Group	
		6501 William Cannon Drive West Austin, TX 78752-9299	
<small>This document contains information proprietary to Freescale Semiconductor and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of Freescale Semiconductor.</small>			
Designer: FRANK L		Drawing Title: BRKTSTBC-P3115	
Drawn by: FRANK L		Page Title: CONTENT	
Approved: Team		Size C	Document Number SCH-28985 PDF: SPF-28985
Date: Tuesday, November 03, 2015		Sheet 1	Rev A
		of 1	of 3

1. Unless Otherwise Specified:

All resistors are in ohms, most are 1%, 1/10 Watt. Otherwise are 5%, 1/8 Watt.

All capacitors are in uF, some are 10% or 20%

All voltages are DC

All polarized capacitors are tantalum

2. Interrupted lines coded with the same letter or letter combinations are electrically connected.

3. Device type number is for reference only. The number varies with the manufacturer.

4. Special signal usage:

_B Denotes - Active-Low Signal

<> or [] Denotes - Vectored Signals

5. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.



ICAP Classification: FCP: FIUC: X PUBI:

Drawing Title: **BRKTSTBC-P3115**


Page Title: **NOTES**

Size	Document Number	Rev
C	SCH-28985 PDF: SPF-28985	A

Date: Tuesday, November 03, 2015 Sheet 2 of 3

EDGE OF BRKOUT BOARD

MPL3115A PRESSURE SENSOR



MPL3115A
I2C ADDRESS: 0xC0



ICAP Classification: FCP: _____ FUC: X PUB: _____	
Drawing Title: BRKTSTBC-P3115	
Page Title: SENSORS	
Size: C	Document Number: SCH-28985 PDF: SPF-28985
Date: Tuesday, November 03, 2015	Sheet 3 of 3